



HDi Runner

UNIQUE BENEFITS

- Adaptive inductance field reading (autotuning)
- Electronic safety protection
- Heating temperature level setting
- User friendly color touch control panels 5"
- Long inductor cable (from 10 m)
- Heavy Duty portable machine
- **Plug and Play** with art. IND16kW/S inductor head



ART - HDi 16kW Runner



10+
inductor
heads extra
on request

**INDUCTOR
HEAD
HANDLE
INCLUDED**

APPLICATIONS

The HDi Runner heat inductors are ideal for a wide range of applications such as:

- Bolts/nuts releasing
- Pin or bearing release and replacement
- Heating for straightening
- Pre-heating before welding
- Bending
- Hardening
- Annealing

OPTIONALS



TIMER



HEAT
SENSOR IRT




PEDAL SWITCH



SHS



WIFI



INDUCTOR HEAD
HANDLE FROM
11kW TO 18kW

OTHER POWERS AVAILABLE

Technical features HDi 16kW Runner



600x600x1140h mm
500x250x280h mm



800x1200x1350h mm



140 KG + 13 KG



Input power 16 kW - 32 A
Electrical connection IEC60309



400V/3PH+T 50



Working frequency 15-30 KHz



8 m Network cable



IP 21 Degree of protection



Main circuit breaker



20lt tank - Liquid cooling system



Hydraulic heat exchanger with fan



CE EAC UK CA Directives and Certification